



BAVARIA

BAVARIA CRUISER 40

Length Overall - 12.35M
Length of Hull - 11.99M
Length of Waterline - 10.75M
Beam - 3.96M
Deep Keel Std (cast iron) - 2.05M
Shallow Keel (cast iron) - 1.65M
Displacement - 8,680kg
Ballast - 2,736kg (cast iron)
Engine (Volvo Penta D1-30) - 20Kw/28HP
Engine Option (Volvo Penta D2-40) - 30Kw/38HP
Water Tank - 210L (Aus Std 360L)
Fuel Tank - 210L
Cabins - 2 (3 option)
Sail area - 82.00sqm
Height in Saloon - 1.97M
Mast height above waterline - 18.68M



2 Cabin layout



3 Cabin layout

Hull & Deck

Hand-laid fiberglass, solid below the waterline
 Kevlar reinforced bow sections
 Side deck and coach roof with anti slip structure
 Bow fitting with anchor roller
 Two steering columns
 Stainless steel pushpit, stainless steel bow pulpit
 Double lifelines
 Six aluminum mooring cleats
 Two self-tailing halyard winches
 Two self-tailing Genoa winches
 Twin Mainsheet
 Two winch handles, lock in
 Sheets and halyards led to cockpit clutches
 Self-draining anchor locker
 Wood on cockpit floor and seats
 Self-draining gas locker
 Stainless steel boarding ladder
 Deck vent
 Manual bilge pump
 Standard cockpit table
 Wooden companionway doors with perspex inserts
 Lowerable bathing platform
 Pedestal mounted compasses
 Cockpit lockers - Port & Starboard

Engine

Volvo Penta D1-30 28hp sail drive
 Two circuit cooling
 Operating hours meter
 Tachometer
 Fuel level indicator
 Fuel filter
 Seawater filter

Interior

Three cabins with double berths
 Varnished mahogany interior
 Saloon with settee and mahogany table
 12V Socket at chart table
 Forward facing chart table with chart storage
 Chart table seat with stowage
 Two burner gas stove with oven
 80L top opening refrigerator - 12V
 Double stainless steel sink
 Galley stowage for dishes and pots
 Waste bin with lid
 Three fire extinguishers
 Fire blanket
 Two manual toilets
 Holding tanks with deck pump out
 Nine opening hatches
 Ten opening ports
 Blinds and flyscreens on hatches in saloon and forward cabins
 Blinds on portlights

Sails & Rigging

Double spreader Selden mast
 Headsail designed for furling system
 Conventionally battened mainsail
 Windex wind direction indicator
 Adjustable backstay

Fresh Water Supply

Water tank 210L (Aus Std 360L)
 Water level indicator
 Electric water pressure pump with filter
 Hot and cold cockpit shower

Electrical System

12 V panel with circuit breakers
 Multi function electronic panel
 Voltmeter
 Navigation lights
 Electric & Manual bilge pump
 230V Shore power supply
 230V sockets in cabins and galley
 Deck light
 Batteries:
 1 x 88-Ah battery for starting
 1 x135-Ah house battery
 40Ah Battery charger

Steering

Lewmar direct drive steering system
 Symmetrical rudder with force balance
 Rudder stock with self-aligning bearings
 Emergency tiller
 Twin steering wheels

Bavaria Yachts Australia Additional Specification

Electric windlass, Anchor + 50m chain
Rodkick boom vang
Shower with electric sump pump
Hot Water - 20 litres
Additional water tank - 150L
UV strip on Genoa
Epoxy barrier and Antifoul
Safety gear and mooring kit
Companionway door cover
Stainless steel gas bottle with Certification

North South Yachting Australia Head Office:
Quays Marina, 1856 Pittwater Road
Church Point NSW 2105

T: +61 (0)2 9998 9600
F: +61 (0)2 9979 3244

www.northsouthyachting.com.au
info@northsouthyachting.com.au

All weights and measurements have been calculated on the basis of construction documents and may vary slightly.
 Graphs and textual descriptions are in accordance with the information supplied by Bavaria Yachtbau GmbH, Germany, and should serve as a guide.
 All details are subject to change without notice. North South Yachting will not be held accountable for changes outwith the company's control.